



Features

- ✓ Profiled perimeter glazing rebates to match existing putty-glazed windows
- ✓ AAMA AW-100 Architectural Performance Class - Grids designed for project-specific wind loads
- ✓ 2-7/8" frame depth with polyamide thermal barrier
- ✓ Mechanically fastened frame and true divided lite (TDL) muntin grid construction, corner-blocked and hydraulically crimped vents
- ✓ 0.094" extrusion wall thickness
- ✓ Fixed; in- or out-swing casement; top-hinged, awning or hopper vents
- ✓ Custom profiles can be designed for panning, perimeter framing or muntins
- ✓ Optional between-glass blinds with 5/8" aluminum slats
- ✓ 18mm and 24mm thermal barrier for energy savings and condensation resistance
- ✓ Dual-color frame finishes
- ✓ Applied muntin grids optional at exterior, interior and/or between glass
- ✓ Panning systems with "T" mullions to echo existing profiles
- ✓ Head, jamb and sill receptors with stacking mullions

Performance

Allowable Air
0.10 cfm/sqft at 6.24 psf
Water
12 psf
NFRC U-Factor
0.38 to 0.73 BTU/hr.sqft.°F (est.)
CRF_f
43 to 58 (est.)
STC
32 to 39 (est.)



NOTE: Performance can vary with hardware and glass package selected.

DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2022 Apogee Wausau Group, Inc.