



Features

- ✓ 2" frame depth with polyurethane thermal barrier (8200 and 8250), 3 ¼" frame depth (8260) or 4" frame depth (8400)
- ✓ AAMA AW-80 Performance Class
- ✓ Fixed, project-out awning, project-in hopper, or casement
- ✓ 0.094" principal wall thickness (0.125" on 8200)
- ✓ Overlap vent construction
- ✓ Side-stacking, self-mating, mullions for ease of installation
- ✓ Corner-blocked and crimped vent construction for durability
- ✓ Dual glazed option with hinged access panels
- ✓ 5/8" between-glass Venetian blinds available
- ✓ Formed aluminum or trim clip anchors
- ✓ Head, sill and jamb receptors available
- ✓ Broad selection of renovation panning

Performance

Allowable Air
0.10 cfm/sqft at 6.24 psf
Water
12 psf
NFRC U-Factor
0.35 to 0.51 BTU/hr.sqft.°F (est.)
CRF_f
48 to 53 (est.)
STC
32 to 39 (est.)



NOTE: Performance can vary with hardware and glass package selected.

DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.