



### Features

- ✓ 3-1/4" frame depth
- ✓ 18 mm, 22 mm and 38 mm XLT polyamide thermal barriers
- ✓ Can accommodate different interior and exterior finishes
- ✓ AAMA AW-50 Architectural Performance Class rating
- ✓ 0.060" to 0.080" extrusion wall thickness
- ✓ Tilt-in sash for custodial cleaning access
- ✓ Rigid, five-member frame construction for ease of installation and lower air infiltration
- ✓ Various latches available; block and tackle or Caldwell Ultralift™ balances
- ✓ Optional snap-in nailing flange/air-water membrane leg
- ✓ Between-glass muntins optional
- ✓ Half screens available, removable from the interior

### Performance

<b>Allowable Air</b>
0.30 cfm/sqft at 6.24 psf
<b>Water</b>
10 psf
<b>NFRC U-Factor</b>
0.38 to 0.53 BTU/hr.sqft.°F
<b>CRF<sub>f</sub></b>
69
<b>STC</b>
33 to 37



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2022 Apogee Wausau Group, Inc.