



Features

- ✓ 3 1/4" frame depth with polyurethane or polyamide thermal barrier
- ✓ Glazed-in or "flat back" frame options
- ✓ Project-out awning or project-out casement only
- ✓ AAMA AW60 Performance Class
- ✓ Mitered frame construction, corner-blocked tubular vents
- ✓ Factory four-side silicone glazed for "no sag" performance, even in large vent sizes
- ✓ 1/8" principal wall thickness
- ✓ Can be used with most projected window occupant-operated locking hardware
- ✓ See 4250-Z Series for multi-lock and vents for structural glazed curtainwall
- ✓ NFRC labeled
- ✓ High recycled content aluminum framing

Performance

Allowable Air
0.10 cfm/sqft at 6.24 psf
Water
15.0 psf
NFRC U-Factor
0.50 to 0.67 BTU/hr.sqft. °F (est)
CRF_f
48 to 53
STC
30 to 34 (est)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.