



Features

- ✓ 5-7/8" frame depth for high spans and wind loads; polyamide thermal barrier
- ✓ Half-slide, end-slide, center-slide, and center-open two-track configurations side-stack with INvent™ fixed lites
- ✓ AAMA "Architectural" Performance Class up to AW100 lift and slide, up to AW90 conventional, and AW40 with accessible threshold (detail shown); all life cycle-tested for durability
- ✓ Easy-to-install, rigidly square, pre-glazed fixed lites independent of door frames
- ✓ Interlocking polyamide insert and stainless steel roller track cross from fixed to sliding side
- ✓ Outside-track for terrace access; inside track for use with integral Juliet balconies
- ✓ Extruded "palm tree" pull handles at side-stacking meeting rails
- ✓ Listed in the National Fenestration Rating Council (NFRC) CMA database

Performance

Allowable Air

0.30
cfm/sqft at 6.24 psf

Water

8 to 12 psf

NFRC U-Factor

0.39 to 0.67
BTU/hr.sqft.°F

CRF_f

57 to 72

STC

33 to 39

OITC

27 to 33



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2017 Apogee Wausau Group, Inc.