

Architectural Windows

2250i/3250i/4250i INvent™ Series

Elevations Viewed From The Exterior

Section Contents

Details	P17-2 thru P17-4
Posts and Stacks	P17-5 thru P17-7
Glazing Options	P17-8
-BHM Blast Mitigation	P17-9
-HP Hurricane Impact	P17-9
Blind Options	P17-10 and P17-11
Simulated Double Hung	P17-12 thru P17-23
Accessories	P17-24 thru P17-27
Isometric Views	P17-28 and P17-29

AAMA Test Configurations (shown)

Architectural AW Class



For air, water, cycling and structural

Fixed Frame Size	60" x 99"	Fixed	1524 mm x 2515 mm
Projected Frame Size	60" x 144"	Type D	1524 mm x 3658 mm
Casement Frame Size	108" x 60"	Type D	2743 mm x 1524 mm
Gateway Sizes	60" x 36"	Projected	1524 mm x 914 mm
	36" x 60"	Casement	914 mm x 1524 mm

NFRC 100 Thermal Test Configurations (shown)

For U-Factor, SHGC and CR

Fixed Frame Size	47" x 59"	1200 mm x 1500 mm
Projected Frame Size	59" x 24"	1500 mm x 600 mm
Casement Frame Size	24" x 59"	600 mm x 1500 mm



2250i/3250i/4250i INvent

Contact A Wausau Representative For Other Possible Configurations





WAUSAU

WINDOW AND WALL
SYSTEMS

Projected and Fixed Details

Architectural Windows

2250i/3250i/4250i INvent™ Series








WAUSAU

WINDOW AND WALL
SYSTEMS

Projected and Fixed Details

Architectural Windows

2250i/3250i/4250i INvent™ Series









WAUSAU

WINDOW AND WALL
SYSTEMS

Projected and Fixed Details

Architectural Windows

2250i/3250i/4250i INvent™ Series






WAUSAU

WINDOW AND WALL
SYSTEMS


Posts and Stacks

Architectural Windows

2250i/3250i/4250i INvent™ Series



Fixed / Fixed Post



Fixed / Fixed

I-values indicated are for frame members only.
Thermal barrier shear reduction of 10% included.




WAUSAU

WINDOW AND WALL
SYSTEMS


Posts and Stacks

Architectural Windows

2250i/3250i/4250i INvent™ Series



Fixed / Project-In



Fixed / Project-Out

I-values indicated are for frame members only.
Thermal barrier shear reduction of 10% included.




WAUSAU

WINDOW AND WALL
SYSTEMS


Posts and Stacks

Architectural Windows

2250i/3250i/4250i INvent™ Series



Project-In Vent / Project-In Vent



Project-Out Vent / Project-Out Vent

I-values indicated are for frame members only.
Thermal barrier shear reduction of 10% included.




WAUSAU

WINDOW AND WALL
SYSTEMS

Glazing Options

Architectural Windows

2250i/3250i/4250i INvent™ Series






WAUSAU

WINDOW AND WALL
SYSTEMS


-BHM Blast and -HP Hurricane Glazing Options

Architectural Windows

2250i/3250i/4250i INvent™ Series



1 1/16" (nom.) Insulating Laminated Glass
Inside Glazed




1 3/16" (nom.) Insulating Laminated Glass
Inside Glazed

-BHM Blast Hazard Mitigation

Peak Pressure and Impulse up to 10 psi - 89 psi-msec
Not available in Simulated Double Hung

Contact Wausau for
blast glazing details
applicable to the
specific requirements
of your project



1 5/16" (nom.) Insulating Laminated Glass
Inside Glazed



WAUSAU


WINDOW AND WALL
SYSTEMS

Blind Options


Architectural Windows

2250i/3250i/4250i INvent™ Series


Elevations Shown As Viewed From The Interior




Lift-Out



1" Blind/Dual Glazed



Hinged



5/8" Blind/Dual Glazed



WAUSAU




WINDOW AND WALL
SYSTEMS

Blind Options


Architectural Windows

2250i/3250i/4250i INvent™ Series


Elevations Shown As Viewed From The Interior



5/8" Blind/Triple Glazed



Lift-Out



Hinged



WAUSAU

WINDOW AND WALL
SYSTEMS




Simulated Double Hung
Panning and T-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series

Non-stocked items shown - Minimum order quantity may apply

Panning and mullions are available in various depths, with optional historic ogee or reverse cove profiles. Refer to "Accessories" for more information.



4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.




WAUSAU

WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Panning and T-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series





WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Panning and T-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series

4250i INvent simulated
double hung windows in
multiple bays must be used in
conjunction with T-mullions or
H-mullions. Side stacking
jambes not available.





WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Panning and T-Mullions

Architectural Windows


2250i/3250i/4250i INvent™ Series

Non-stocked items shown – Minimum order quantity may apply



6

4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.



7

Panning and mullions are available in various depths, with optional historic ogee or reverse cove profiles. Refer to "Accessories" for more information.



WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions



Architectural Windows

2250i/3250i/4250i INvent™ Series

Head, jamb and sill starters are available in a number of face widths and water head heights. Please refer to "Series Accessories" for more information.



4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.






WAUSAU

WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series





WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series

4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.





WAUSAU

WINDOW AND WALL
SYSTEMS


Simulated Double Hung
Starters and H-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series


Non-stocked items shown – Minimum order quantity may apply

4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.



6

Head, jamb and sill starters are available in a number of face widths and water head heights. Please refer to "Series Accessories" for more information.



7



WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions



Architectural Windows

2250i/3250i/4250i INvent™ Series

Head, jamb and sill starters are available in a number of face widths and water head heights. Please refer to "Series Accessories" for more information.



4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.






WAUSAU

WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series





WAUSAU


WINDOW AND WALL
SYSTEMS

Simulated Double Hung
Starters and H-Mullions

Architectural Windows

2250i/3250i/4250i INvent™ Series

4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.





WAUSAU

WINDOW AND WALL
SYSTEMS


Simulated Double Hung
Starters and H-Mullions

Architectural Windows


2250i/3250i/4250i INvent™ Series

Non-stocked items shown - Minimum order quantity may apply

4250i INvent simulated double hung windows in multiple bays must be used in conjunction with T-mullions or H-mullions. Side stacking jambs not available.



6



7

Head, jamb and sill starters are available in a number of face widths and water head heights. Please refer to "Series Accessories" for more information.




WAUSAU

WINDOW AND WALL
SYSTEMS


Accessories
Head, Jamb and Sill Starters

Architectural Windows


2250i/3250i/4250i INvent™ Series




2250i Head & Jamb Starter




2250i Sill Starter




3250i Head & Jamb Starter



3250i Sill Starter



4250i Head & Jamb Starter



4250i Sill Starter

Value in psf Indicates Approximate Water Head Performance
Other Sill Starters Available For Higher Water Test Pressures




WAUSAU

WINDOW AND WALL
SYSTEMS


Accessories
Anchors

Architectural Windows


2250i/3250i/4250i INvent™ Series



2250i Slide-In Anchor
1/8" (nom.) Formed Steel



3250i Heavy Duty Slide-In Anchor
3/16" (nom.) Formed Steel



4250i Heavy Duty Slide-In Anchor
3/16" (nom.) Formed Steel



WAUSAU


WINDOW AND WALL
SYSTEMS

Accessories
Frame Extenders and Caulk Backers


Architectural Windows

2250i/3250i/4250i INvent™ Series


Non-stocked items shown – Minimum order quantity may apply




Frame Extender
Trim to Fit



2250i



3250i



4250i

PVC Caulk Backers



WAUSAU


WINDOW AND WALL
SYSTEMS

Accessories
Optional Nailing Fin Anchor

Architectural Windows

2250i/3250i/4250i INvent™ Series

Non-stocked items shown – Minimum order quantity may apply



**Nailing Fin
Exterior Anchor**



WAUSAU

WINDOW AND WALL
SYSTEMS

Exploded Starter System Installation

Architectural Windows

2250i/3250i/4250i INvent™ Series


Key:

- 1 Extruded Aluminum Head And Jamb Starter With Polyamide Thermal Barrier
- 2 Extruded Aluminum Sill Starter With Polyamide Thermal Barrier
- 3 Drive-On Starter Strip
- 4 Structural Attachment May Vary Per Conditions - Field Seal All Fastener Heads
- 5 Erector Installed Full-Bearing Shims
- 6 Aluminum Splices With Bond Breaker Tape - Erector Set In Sealant and Exterior Applied Sealant Joint
- 7 Aluminum Splice - Erector Set In Sealant
- 8 Erector Installed And Tooled Expansion / Splice Joint
- 9 Foam Baffle Weep Back-Up
- 10 Perimeter Sealant Joint, Specified Sealant And Backer Rod
- 11 Insulation
- 12 Stone Lintel
- 13 Brick
- 14 Interior Concrete Block

Note: Installation Conditions Vary...

2250i INvent Series Shown

-XLT Similar





WAUSAU

WINDOW AND WALL
SYSTEMS

Exploded Window Installation

Architectural Windows

2250i/3250i/4250i INvent™ Series

Frames

- 1 Extruded Frame Extender (When Required)
- 2 PVC Caulk Backer
- 3 Specified Rod And Perimeter Sealant
- 4 Erector Dead Load Shim

Anchorage (Using Slide-In Anchors)

- 5 Stainless Steel Fasteners Suitable For Substrate Material
- 6 Steel Slide-In Anchor With Fasteners (When Required At 3 1/2" And 4 1/2" Depth Systems)

Perimeter

- 7 Brick
- 8 Flashing
- 9 Insulation
- 10 Always Maintain Vapor Barrier Between Frame And Adjacent Walls
- 11 General Contractor Provide Blocking To Secure Attachment Into Steel Studs
- 12 Erector Installed Full-Bearing Shim

2250i INvent Series Shown

-XLT Similar

