



Features

- ✓ 4-1/2" frame depth
- ✓ 24 mm and 38 mm XLT polyamide thermal barriers
- ✓ Can accommodate different interior and exterior finishes
- ✓ AAMA AW-45 Architectural Performance Class or optional AW-80 rating
- ✓ Fixed, half-slide, end-slide or center-slide configurations
- ✓ 0.060" to 0.090" extrusion wall thickness
- ✓ Rigid, five-member frame construction for ease of installation and lower air infiltration
- ✓ Concealed plunger lock, flush mounted actuating handle, and ball bearing rollers on a raised track
- ✓ Optional frame cavity foam fillers and triple insulating glass
- ✓ Half screens available, removable from the interior
- ✓ Head, sill and jamb receptors available; broad selection of renovation panning
- ✓ NFRC Listed

Performance

Allowable Air
0.30 cfm/sqft at 6.24 psf
Water
15 psf
NFRC U-Factor
0.31 to 0.53 BTU/hr.sqft.°F
CRF_f
69
STC
33 to 37



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2022 Apogee Wausau Group, Inc.