



Performance

Features

- ✓ 2 1/2", 3 1/2" and 4 1/2" frame depth with polyurethane thermal barrier
- ✓ AAMA AW-70 Performance Class
- ✓ Fixed, project-out awning, project-in hopper, or casement
- ✓ Flush vent construction reduces collection of dust and debris
- ✓ Dual or triple glazed option with hinged or lift-out access panels
- ✓ 5/8" or 1" between-glass Venetian blinds available
- ✓ Twist-in or slide-in heavy duty steel anchors
- ✓ 1/8" principal wall thickness
- ✓ Head, sill and jamb receptors available
- ✓ Broad selection of renovation panning
- ✓ Offered through Advantage by Wausau
- ✓ NFRC labeled
- ✓ High recycled content aluminum framing

Allowable Air

0.10
cfm/sqft at 6.24 psf

Water

12 psf

NFRC U-Factor

0.35 to 0.63
BTU/hr.sqft.°F

CRF_i

44 to 55

STC

34 to 43



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Wausau