



## Features

- ✓ 2700-HSD, 4½" frame depth with non-structural thermal barrier
- ✓ 2760-HSD, 6¾" frame depth with optional sound absorption design
- ✓ AAMA HS-DW-HC40 rated
- ✓ Two-color finish options
- ✓ Various glazing infills available
- ✓ Low maintenance, easy cleaning, smooth operation, indirect ventilation
- ✓ Marine glazed with reusable welded corner gaskets
- ✓ Automatic plunger lock at the meeting rail
- ✓ "Slide-by" custodial operation for cleaning
- ✓ 5/8" or 1" between-glass Venetian blinds available
- ✓ Broad selection of renovation panning
- ✓ High recycled content aluminum framing

## Performance

<b>Allowable Air</b>
0.37 cfm/sqft at 1.57 psf
<b>Water</b>
8 psf
<b>NFRC U-Factor</b>
0.56 BTU/hr.sqft.°F (est.)
<b>CRF<sub>f</sub></b>
56 (est.)
<b>STC</b>
38 to 48 (est.)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.