

3100 Series *HUNG* Windows



PERFORMANCE

- AW60 Double Hung
- 12 PSF Water Test Pressure
- L/175 Deflection Limits
- Life Cycle Tested per AAMA 910
- 60 PSF Design Load /90 PSF Structural Load
- Polyurethane Thermal Barrier Design
- 10 Year Warranty
- Matching AW40 Horizontal Rolling
(Downsize and reinforced testing to AW60)



WAUSAU

WINDOW AND WALL
SYSTEMS



STANDARD CONSTRUCTION

BENEFITS

- Designed for minimum factory labor and ease of installation
 - Self-mulling (stacking) frame members; 4-1/2" frame depth
 - Mates with any Wausau 4-1/2" system (e.g. 450T fixed and projected)
 - BSI block and tackle balances
 - Sweep lock at meeting rail
 - Bead glazed/integral pulls
 - Mitered, corner blocked and crimped sash/Uniform weatherstripping thickness
 - Common componentry and matching sitelines in horizontal rolling and side load hung products
 - 0.078" wall thickness typical (0.094" thickness at sill webs)
 - Flush screen frame
 - Uses standard Wausau lift-out **or hinged** access sash (similar to 2250 and 250T)
 - Common frame transoms and spandrels
- Competitive and timely
 - No field sealed mullions and clips; minimum jobsite handling
 - Combines with other window types
 - Quad balances available for heavy sash
 - Glass replacement without removing sash
 - For torsional stiffness, long term durability
 - Resistant to local loads and impacts
 - Attractive appearance — no protrusions to collect debris

OPTIONS



- Uses all standard Wausau 4-1/2" installation accessories (starters, receptors, caulk stops, etc.)
- Integral Venetian blinds
- Muntins
- Full or half screens
- Limit stops
- Auto locks at head and/or sill
- 3150 Series tilt sash design with matching sitelines
- Historical glazing rebates and muntin grids
- Caldwell Ultra-lift™ balances
- Two color finish
- Fixed sash single hung

7800 International Drive Wausau, WI 54401
Toll Free 1 877 678 2983 Fax 1 715 843 4350
Email info@wausauwindow.com



WAUSAU
WINDOW AND WALL
SYSTEMS