



## Features

- ✓ 3½" frame depth with polyamide thermal barrier
- ✓ Up to AAMA AW100 Performance Class
- ✓ Rigid "five-member" frame construction for ease of installation
- ✓ Sturdy corner-blocked and crimped sash construction
- ✓ Extruded aluminum or slide-in steel anchors
- ✓ Meeting rail or sill latches
- ✓ Accepts 1" insulating glass; bead glazed
- ✓ Block and tackle or Ultralift® balances
- ✓ Head, sill and jamb receptors available
- ✓ Broad selection of renovation panning
- ✓ Offered through Advantage by Wausau
- ✓ Check out [www.wausauwindow.com](http://www.wausauwindow.com) for double hung, tilt sash and blinded options
- ✓ High recycled content aluminum framing

## Performance

<b>Allowable Air</b>
0.30 cfm/sqft at 6.24 psf
<b>Water</b>
12 psf
<b>NFRC U-Factor</b>
0.45 to 0.61 BTU/hr.sqft.°F
<b>CRF<sub>f</sub></b>
59
<b>STC</b>
33 (est)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Wausau