



Features

- ✓ 4" frame depth with polyamide nylon thermal barrier
- ✓ AAMA AW-120 air, water and structural performance
- ✓ Fixed or side-hinged in-swing casements for cleaning or custodial ventilation
- ✓ Mitered and corner-blocked frame and vent construction
- ✓ No vent joinery exposed to the exterior
- ✓ Concealed hinges
- ✓ 1/8" principal wall thickness
- ✓ Triple glazed with internal hinged access panels (dual glazed optional)
- ✓ 5/8" or 1" between-glass Venetian blinds available
- ✓ High recycled content aluminum framing

Performance

Allowable Air
0.10 cfm/sqft at 6.24 psf
Water
15.0 psf
NFRC U-Factor
0.34 to 0.39 BTU/hr.sqft.°F
CRF_i
57 to 60
STC
42 to 48



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau group, Inc.