


Test Unit Elevations

Architectural Windows

4100i-HS Double Slide and Fixed Series

Elevations Viewed From The Exterior

Section Contents	Page(s)
Details Mullion Stacks Glazing Options Accessories	S2-5 S2-6



AAMA Test Configurations (shown) Architectural AW Class


For air, water, cycling and structural

Fixed Frame Size	59" x 98"	Fixed	1500 mm x 2500 mm
Horizontal Slider Size	98" x 79"	Type B	2500 mm x 2000 mm

NFRC 100 Thermal Test Configurations (shown)

For U-Factor, SHGC and CR

Fixed Frame Size	47" x 59"	1200 mm x 1500 mm
Horizontal Slider Size	59" x 47"	1500 mm x 1200 mm






4100i-HS

Contact A Wausau Representative For Other Possible Configurations.



Sliding and Fixed Details


4100i-HS Series







Sliding and Fixed Details

4100i-HS Series








I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.



Sliding and Fixed Details

4100i-HS Series




I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.



Posts and Stacks

4100i-HS Series




I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.




Glazing Options

4100i-HS Series



1" Insulating Glass Operable Inside Glazed




1" Insulating Glass Fixed Inside Glazed




Accessories Head, Jamb, and Sill Starters

4100i-HS Series



4250i Head & Jamb Starter





4250i Sill Starter




Accessories Anchor Options

4100i-HS Series







Twist-In Anchor 1/8" Formed Steel

