



Features

- ✓ 3½" frame depth with polyamide thermal barrier
- ✓ AAMA AW45 and AW70 Performance Class
- ✓ Rigid "five-member" frame construction for ease of installation
- ✓ Accepts 1" insulating glass; bead glazed
- ✓ Sturdy corner-blocked and crimped sash construction
- ✓ Extruded aluminum or twist-in steel anchors
- ✓ Ball bearing Delrin® rollers
- ✓ Automatic spring-loaded jamb latches
- ✓ Head, sill and jamb receptors available
- ✓ Broad selection of renovation panning
- ✓ Offered through Advantage by Wausau
- ✓ Recycled aluminum framing available upon request

Performance

Allowable Air
0.30 cfm/sqft at 6.24 psf
Water
12 psf
NFRC U-Factor
0.45 to 0.65 BTU/hr.sqft.°F (est)
CRF_f
55 (est)
STC
32 (est)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Wausau