



Features

- ✓ 4" frame depth
- ✓ Available for two- or four-side structural glazed curtainwall of varying face widths
- ✓ Project-out awning or project-out casement only
- ✓ Multi-point locking system for single handle operation
- ✓ AAMA AW90 (Awning) AW100 (Casement) air, water and structural performance
- ✓ Mitered frame construction, corner-blocked tubular vents
- ✓ Factory four-side silicone glazed for "no sag" performance, even in large vent sizes
- ✓ 1/8" principal wall thickness
- ✓ Concealed stainless steel four-bar friction hinges only
- ✓ NFRC labeled
- ✓ High recycled content aluminum framing

Performance

Allowable Air	0.10 cfm/sqft at 6.24 psf
Water	15.0 psf
NFRC U-Factor	0.39 to 0.72 BTU/hr.sqft.°F
CRF_f	67 to 68
STC	30 to 34 (est)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.