


Window Wall - 4250i-XLT INvent™ Series

Elevation Viewed From The Exterior



NFRC 100 Thermal Test Configurations


(Refer to 4250i-XLT window details) For U-Factor, SHGC and CR

Fixed Frame Size 47" x 59" Projected Frame Size 59" x 24" Casement Frame Size 24" x 59"


4250i-XLT INvent Window Wall


Contact A Wausau Representative For Other Possible Configurations






















Window Wall - 4250i-XLT INvent™ Series




Fixed / Fixed Post



I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.




Window Wall - 4250i-XLT INvent™ Series



(16) Fixed / Project-In Lock Side


(17) Fixed / Project-In Hinge Side




Fixed / Project-Out

I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.

Window Wall - 4250i-XLT INvent™ Series




Project-In Vent / Project-In Vent



Project-Out Vent / Project-Out Vent


I-values indicated are for frame members only. Thermal barrier shear reduction of 10% included.






1" Insulating Glass
Inside Glazed

1 3/4" Triple Insulating Glass
Inside Glazed




2" Panel Inside Glazed

1" Spandrel
Outside/Inside Glazed





Glazed-In Muntin Grids
Outside Glazed



Glazed-In Muntin Grids
1" Insulating Glass

Window Wall - 4250i-XLT INvent™ Series






1 1/16" (nom.) Unbalanced Insulating Glass Inside Glazed

1 3/16" (nom.) Insulating Laminated Glass Inside Glazed

Contact Wausau for acoustic glazing details applicable to the specific requirements of your project




1" (nom.) Insulating Glass in VX Sash
"No Sag" Structural Silicone Glazed (SSG)



Window Wall - 4250i-XLT INvent™ Series


Elevations Shown As Viewed From The Interior







Window Wall - 4250i-XLT INvent™ Series

Elevations Shown As Viewed From The Interior










5/8" Blind/Triple Glazed











Decorative Slab Cover Options (Examples)




4250i-XLT Outside 90 Degree Corner



Window Wall - 4250i-XLT INvent™ Series




4250i-XLT H-Mullion at Partitions






Window Wall - 4250i-XLT INvent™ Series




4250i-XLT Head Starter

4250i-XLT 15 psf Sill Starter

Head, jamb and sill starters are available in a number of face widths and water head heights. Please refer to "Series Accessories" and Wausau guide specifications for more information.



4250i-XLT 10 psf Sill Starter




4250i-XLT 6 psf Sill Starter


Value in psf Indicates Approximate Water Head (Without Pressure Equalization) Other Sill Starters Available For Higher or Lower Water Test Pressures

Window Wall - 4250i-XLT INvent™ Series

Non-stocked items shown - Minimum order quantity may apply



4250i-XLT Heavy Duty Slide-In Anchor 3/16" (nom.) Formed Steel



PVC Caulk Backers