



Features

- ✓ 4 1/2" frame depth with polyurethane thermal barrier
- ✓ AAMA AW60 Performance Class
- ✓ Low maintenance and smooth operation
- ✓ "Inside slide" design with flush exterior screen track
- ✓ Available in half slide, center slide, end slide or center open configurations
- ✓ Accepts 1" insulating glass; bead glazed
- ✓ Sturdy corner-blocked and crimped door leaf construction
- ✓ Adjustable grease-packed ball bearing rollers
- ✓ Hinged or lift-off access doors optional
- ✓ 5/8" between-glass Venetian blinds available
- ✓ Head and jamb receptors available
- ✓ Offered through Advantage by Wausau
- ✓ NFRC labeled
- ✓ High recycled content aluminum framing

Performance

Allowable Air	0.30 cfm/sqft at 6.24 psf
Water	12 psf
NFRC U-Factor	0.47 to 0.67 BTU/hr.sqft.°F
CRF_f	49 to 53
STC	33 to 38



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.