



## Features

- ✓ 2 7/8", 3 7/8" and 4 7/8" frame depth with extra-wide polyamide thermal barrier
- ✓ AAMA AW-100 Performance Class
- ✓ Fixed, project-out awning, project-in hopper, or casement
- ✓ Flush vent construction reduces collection of dust and debris
- ✓ Glazed-in grid muntins available for historical renovation
- ✓ 4250i-XLT simulated double hung option
- ✓ Dual or triple glazed option with hinged or lift-out access panels
- ✓ 5/8" or 1" between-glass Venetian blinds available
- ✓ Slide-in heavy duty steel anchors
- ✓ 1/8" principal wall thickness
- ✓ Multi-lock hardware option for improved accessibility
- ✓ Head, sill and jamb receptors available
- ✓ Broad selection of renovation panning
- ✓ Offered through Advantage by Wausau
- ✓ NFRC labeled
- ✓ High recycled content aluminum framing
- ✓ BHM option for UFC or ISC blast hazard mitigation
- ✓ HP option for ASTM 1996 hurricane impact resistance (3250i-XLT and 4250i-XLT only)

## Performance



<b>Allowable Air</b>
0.10 cfm/sqft at 6.24 psf
<b>Water</b>
15 psf
<b>NFRC U-Factor</b>
0.21 to 0.60 BTU/hr.sqft.°F
<b>CRF<sub>f</sub></b>
59 to 71 (est.)
<b>STC</b>
31 to 43



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Wausau