



Now available: Composite 2 1/2" pressure plate XLT option for improved thermal performance

Features

- ✓ Wausau's flagship curtainwall product line
- ✓ Several frame depths including cladding for steel tubes
- ✓ 2 1/2" or 3" exterior sight line - Many accent covers available
- ✓ 3/8" thermal separation
- ✓ Proven pressure-plate system designed for field glazing
- ✓ Captured or two-side structural glazed
- ✓ Splayed mullions available for segmented radii
- ✓ Screw-spline construction
- ✓ "F" and "T" perimeter anchors
- ✓ Zero sight line vents available
- ✓ Available with interior access doors and between-glass blinds
- ✓ Exterior sun shades and interior light shelves available
- ✓ NFRC and Component Modeling Approach (CMA) listed
- ✓ Recycled aluminum framing available upon request

Performance

Allowable Air
0.06 cfm/sqft at 6.24 psf
Water
15 psf
NFRC U-Factor
0.36 to 0.76 BTU/hr.sqft.°F (est)
CRF_i
67 to 78
STC
31 to 37



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. ©2014 Apogee Wausau Group, Inc.