
SUPERWALLTM SSG Series

Section Contents	Page(s)
Details	C11-2
Mullions	C11-3 and C11-4
Corners	C11-5 and C11-6
Project-Out Vent Details	C11-7
Door Frame Insert	C11-8
Trim Covers	. C11-9 and C11-10
Sun Shade Bracket	. C11-11
Mullion Splices	. C11-12
Glazing Options	. C11-13
Anchorage Isometrics	.C11-14a through C11-15




SuperWall™SSG Four-Side Silicone Glazed




SUPERWALLTM SSG Series

Non-stocked items shown — Minimum order quantity may apply



Perimeter Frame




2 Vision/Spandrel Intermediate


lyy-Values are for Wind Load



SUPERWALLTM SSG Series




SUPERWALLTM SSG Series





SUPERWALL™ SSG Series






SUPERWALLTM SSG Series


Non-stocked items shown - Minimum order quantity may apply $I_x = 34.91 \text{ in}^4$ $I_x = 33.52 \text{ in}^4$ Inside 90 Deg Corner 6 $I_x = 21.68 \text{ in}^4$ $I_x = 12.83 \text{ in}^4$ 5 1/4" - 1/4" (133.35 mm) 6 3/4" (171.4 mm) 7 3/4" (196.8 mm) 8 3/4" (222.2 mm) 10 3/4" (273.0 mm)

SUPERWALLTM SSG Series



7 4250-Z Insert Vent

SUPERWALLTM SSG Series




8 Door Frame Insert



SUPERWALLTM SSG Series

Non-stocked items shown — Minimum order quantity may apply



Non-standard deep exterior snap-on covers (those extending more than 2" from the face of glass) may need to be secured by methods other than snap fits. It is the responsibility of the installer to verify applied loads from maintenance equipment, staging, scaffolding or other exterior access devices, regardless of whether such requirements are included in contract documents, and add mechanical attachment provisions as necessary. Wausau's structural engineering department is available to assist in analysis of loading. Dynamic wind loads, as well as the potential for build-up of ice or snow, should also be considered.


⚠ - OBSOLETE TOOLING STATUS





SUPERWALLTM SSG Series

Non-stocked items shown — Minimum order quantity may apply

2¹/₂" Accent Trim Covers







Non-standard deep exterior snap-on covers (those extending more than 2" from the face of glass) may need to be secured by methods other than snap fits. It is the responsibility of the installer to verify applied loads from maintenance equipment, staging, scaffolding or other exterior access devices, regardless of whether such requirements are included in contract documents, and add mechanical attachment provisions as necessary. Wausau's structural engineering department is available to assist in analysis of loading. Dynamic wind loads, as well as the potential for build-up of ice or snow, should also be considered.


⚠ - OBSOLETE TOOLING STATUS



SUPERWALLTM SSG Series


I-values indicated are for frame members only.

Non-stocked items shown — Minimum order quantity may apply



(10) Sunshade Attachment

SUPERWALLTM SSG Series




SW Mullion Splice



SUPERWALLTM SSG Series


Non—stocked items shown — Minimum order quantity may apply



Contact A Wausau Representative For Other Possible Glazing Options.




SUPERWALLTM SSG Series






SUPERWALLTM SSG Series






SUPERWALLTM SSG Series





SUPERWALLTM SSG Series

Shown with SuperWall glazing



Typical Connection

Bolt *

Washer

Pipe Spacer

4 Nut

5 Steel Angles *

1/8" PVC Plates, Size equals the bearing surface of the anchor.

Heavy Extruded Aluminum Frame Members

8 Expansion Anchor * Concrete Floor Slab Typ.

Typical Holes

Anchorage Hole, (Wausau supplies all holes [10] in steel. Erector to match drill aluminum.)

<u>11</u> Steel To Receive Slots At Live Load

[12] Steel To Receive Clear Holes At Dead Load

^{*} Note: Steel angle, expansion anchor, and thru bolts vary due to wind loads, slab location, and floor height.