



## Features

- ✓ 4½" frame depth with polyamide thermal barrier – Integrates with other Wausau products
- ✓ AAMA AW60 (single) AW50 (French) Performance Class
- ✓ In-swing or out-swing operation
- ✓ Sturdy corner-blocked and crimped door leaf construction; tested in door leaf sizes up to 4'-0" x 8'-0"
- ✓ Verona-style handle with manual compression lock; adjustable stainless steel multi-point locks
- ✓ Designed for LCN 4040 door closers (by others)
- ✓ Improved access sills (limited water) available for single and French doors
- ✓ Forced entry resistant
- ✓ Two-color finish option
- ✓ Window wall insert frames available
- ✓ Offered through Advantage by Wausau
- ✓ High recycled content extruded framing

## Performance

<b>Allowable Air</b>
0.10 cfm/sqft at 6.24 psf
<b>Water</b>
15 psf (single) 12 psf (French)
<b>NFRC U-Factor</b>
0.47 to 0.67 BTU/hr.sqft.°F (est)
<b>CRF<sub>f</sub></b>
58
<b>STC</b>
33 to 37 (est)



DISCLAIMER: Wausau Window and Wall Systems takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Wausau's sole discretion. © 2014 Apogee Wausau Group, Inc.